



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

List of Products Covered in Our PCC LP

Aluminium Armoured / Unarmoured Cables

Copper Armoured / Unarmoured Cables

HT Cables

Instrumentation Cables

Rubber Cables

JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables

RS 485 Cables

Fire Survival Cables

FS Aluminium Cables



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		96	108		125
4		110	126		146
6		129	149		172
10		157	188		202
16	106	178	194		240
25	139	208	261	302	322
35	164	257	339	373	411
50	199	317	444	482	548
70	254	424	571	648	736
95	275	543	719	815	929
120	333	649	856	1014	1142
150	392	781	1058	1181	1382
185	479	943	1296	1495	1737
240	625	1225	1639	1903	2176
300	769	1494	2049	2315	2699
400	970	1837	2621	2978	3403
500	1185	2435	3287	3820	4407
630	1459	3064	4367	5208	5932
800	1818				
1000	2297				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	25%
- 3 x 16 & 3.5CX25 & above	25%
- 4 x 10 & above	25%
- For Single core 95 & above	25%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	5%
Extruded PVC Innersheath 70 & Above	2.5%
d) HR PVC Insulation	10%
e) HR PVC Inner Sheath	5%
f) HR PVC Outer Sheath	5%
g) Oxygen Index (FR)	2.5%
h) PVC Insulated Cables	8%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
	Power (Al.)			
Upto 16	10%	7.5%	15%	20%
25 - 50	7.5%	7.5%	12.5%	15%
70 & above	5%	5.0%	15%	12.5%
	Power Single Core (Al.)			
Upto 16	-N.A-	10%	-N.A-	25%
25 - 50	-N.A-	10%	-N.A-	20%
70 & above	-N.A-	7.5%	-N.A-	17.5%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		64	81		95
6		79	101		119
10		112	136		152
16	58	123	153		191
25	91	164	226	283	298
35	111	225	308	340	369
50	143	274	386	442	493
70	189	378	531	607	697
95	243	468	663	765	857
120	290	572	811	981	1026
150	350	683	995	1155	1294
185	429	823	1221	1457	1592
240	520	1094	1563	1761	2072
300	648	1337	1936	2238	2481
400	813	1668	2396	2844	3264
500	1064	2032	3133	3684	4171
630	1336	2588	4199	5002	5681
800	1697				
1000	2183				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	5%
Extruded PVC Innersheath 70 & Above	2.5%
c) HR PVC Insulation	10%
d) HR PVC Inner Sheath	5%
e) HR PVC Outer Sheath	5%
f) Oxygen Index (FR)	2.5%
g) PVC Insulated Cables	8%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
		Power (Al.)		
Upto 16	10%	7.5%	15%	20%
25 - 50	7.5%	7.5%	12.5%	15%
70 & above	5%	5%	15%	12.5%
		Power Single Core (Al.)		
Upto 16	-N.A-	10%	-N.A-	25%
25 - 50	-N.A-	10%	-N.A-	20%
70 & above	-N.A-	7.5%	-N.A-	17.5%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		229	301	390	488	578	662
6		314	421	568	683	903	1029
10		497	679	855	1108		
16	442	688	965	1265	1680		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY		Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	125	176	14	515	799
3	159	218	16	572	901
4	193	272	19	670	1032
5	234	327	24	839	1295
6	262	387	27	931	1447
7	290	438	30	1024	1624
8	336	503	37	1246	1990
10	406	574	44	1514	2459
12	450	672	61	2067	3353

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.50%
D) Round Wire Armouring	
1C x 95 sq. mm & above	7.50%
1.5 sq.mm - 12 core & above	15%
2.5 sq.mm - 9 core & above	15%
10 sq.mm - 4 core & above	15%
16 sq.mm - 2 core & above	15%
16 sq.mm - 3 core & above	15%
E) OXYGEN INDEX (FR)	2.50%
F) HR PVC Insulatoin	7%
HR I/S & O/S	5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	7.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
H) PVC Insulated Cables	5%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
2 to 4 Core	5%	6%	15%	15%
5 to 10 Core	5%	4%	15%	15%
12 & Above	5%	4%	12.50%	12.50%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core
	2XY	2XY	2XY	2XY
4		194	271	340
6		277	389	496
10		479	656	775
16	370	629	925	1180

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	92	136	14	426	760
3	121	182	16	507	864
4	155	238	19	599	995
5	192	293	24	760	1259
6	216	332	27	838	1393
7	247	398	30	981	1507
8	296	458	37	1182	1862
10	367	521	44	1396	2237
12	383	641	61	1968	3051

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.5%
D OXYGEN INDEX (FR)	2.5%
E) HR PVC Insulation	7%
HR PVC I/S & O/S	5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	7.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
G) PVC Insulated Cables	5%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
Unarmd				
2 - 4	5%	6%	15%	15%
5 - 10	5%	4%	15%	15%
12 & Above	5%	4%	12.5%	12.5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	638	1089	1536	1788	1974	2550
35	842	1484	2073	2377	2926	3815
50	1162	1972	2872	3325	3810	5200
70	1622	2752	4159	4860	5669	
95	2045	3678	5763	6721	7661	
120	2609	4510	7375	8725	9760	
150	3198	5648	8457	10619	12396	
185	3911	6992	11366	13414	15260	
240	4986	9007	14884	17384	19848	
300	6298	11407	18664	21730	24851	
400	8449	15519	25206	29072	33867	
500	10450					
630	13136					
800	16628					
1000	20901					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	556	1054	1451	1570	1854	
35	740	1410	1939	2242	2776	
50	1039	1898	2702	3185	3562	
70	1461	2544	3947	4674	5424	
95	1953	3471	5643	6688	7400	
120	2512	4367	6895	8586	9332	
150	3090	5465	8095	10245	12139	
185	3828	6742	10708	12678	15180	
240	4931	8632	14314	16799	19654	
300	6202	10755	17661	20649	23653	
400	8155	14356	23150	26725	31720	
500	10380					
630	13067					
800	16552					
1000	20692					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.50%
D) Round Wire Armouring	
1C x 95 sq. mm & above	7.50%
10 sq.mm - 4 core & above	15%
16 sq.mm - 2 core & above	15%
16 sq.mm - 3 core & above	15%
E) OXYGEN INDEX (FR)	2.50%
F) HR PVC Insulation	7%
HR I/S & O/S	5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
H) PVC Insulated Cables	5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, it may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

Size in Sq.mm.	(Rate in Rs. Per Mtr.)					
	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		842				
50		966				
70	1078	1148				
95	1257	1374	1816	1904	2516	
120	1482	1586	2087	2154	2762	
150	1686	1778	2299	2407	3051	3481
185	1957	2077	2610	2714	3379	3867
240	2381	2499	3074	3185	3852	4369
300	2849	2964	3553	3662	4350	4898
400	3539	3620	4209	4393	5062	5665

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	3%
2) Pressure Extruded PVC Innersheath	13%
3) Round Wire Armouring - Up to 11 KV (E)	25%
11 KV (UE) & Above	27.5%
4) FRLS PVC Inner Sheath	5%
5) FRLS PVC Outer Sheath	5%
6) FR Sheath with Oxygen Index	3%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

**POLYCAB INDIA LIMITED**

PCC LP No. 03/2021-22 Dtd : 17th August 2021

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	847	889	931	977	1054	1110	1079	1136	1387	1462	1589	1674
300	970	1024	1068	1127	1201	1264	1229	1293	1640	1729	1766	1860
400	1180	1243	1281	1347	1426	1500	1458	1533	1882	1977	1992	2095
500	1506	1586	1561	1640	1792	1884	1792	1884	2217	2336	2311	2436
630	1818	1916	1868	1965	2117	2225	2117	2225	2578	2714	2685	2825
800	2261	2377	2292	2479	2535	2669	2535	2669	3052	3212	3185	3349
1000	2674	2815	2937	3094	3142	3304	3142	3304	3734	3916	4015	4225

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	7.5%
2) FRLS PVC Outer Sheath	5%
3) Oxygen Index	3%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

**POLYCAB INDIA LIMITED**

PCC LP No. 03/2021-22 Dtd : 17th August 2021

POLYCAB INSTRUMENTATION CABLESStr/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES**

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	105	0.75	121	1	136	1.5	163	2.5	223
CORE	3	0.5	125	0.75	151	1	171	1.5	212	2.5	294
CORE	4	0.5	141	0.75	169	1	199	1.5	249	2.5	355
CORE	5	0.5	157	0.75	194	1	229	1.5	291	2.5	424
CORE	6	0.5	177	0.75	223	1	268	1.5	336	2.5	502
CORE	7	0.5	191	0.75	245	1	294	1.5	384	2.5	574
CORE	8	0.5	215	0.75	275	1	332	1.5	438	2.5	651
CORE	10	0.5	249	0.75	325	1	397	1.5	527	2.5	800
CORE	12	0.5	281	0.75	369	1	452	1.5	611	2.5	907
CORE	14	0.5	320	0.75	413	1	516	1.5	712	2.5	1069
CORE	16	0.5	350	0.75	461	1	575	1.5	788	2.5	1195
CORE	19	0.5	396	0.75	526	1	667	1.5	901	2.5	1413
CORE	24	0.5	479	0.75	634	1	804	1.5	1116	2.5	1761
PAIR	1	0.5	105	0.75	121	1	136	1.5	163	2.5	223
PAIR	2	0.5	153	0.75	185	1	213	1.5	263	2.5	375
PAIR	3	0.5	185	0.75	230	1	275	1.5	345	2.5	510
PAIR	4	0.5	220	0.75	280	1	338	1.5	443	2.5	663
PAIR	5	0.5	255	0.75	330	1	400	1.5	535	2.5	812
PAIR	6	0.5	293	0.75	380	1	465	1.5	625	2.5	943
PAIR	7	0.5	323	0.75	420	1	525	1.5	720	2.5	1080
PAIR	8	0.5	360	0.75	475	1	590	1.5	798	2.5	1215
PAIR	10	0.5	433	0.75	570	1	715	1.5	973	2.5	1495
PAIR	12	0.5	490	0.75	640	1	833	1.5	1140	2.5	1760
PAIR	14	0.5	540	0.75	748	1	945	1.5	1318	2.5	2028
PAIR	16	0.5	615	0.75	825	1	1068	1.5	1470	2.5	2305
PAIR	19	0.5	700	0.75	975	1	1243	1.5	1720	2.5	2700
PAIR	24	0.5	875	0.75	1223	1	1548	1.5	2163	2.5	3393
TRIAD	1	0.5	127	0.75	153	1	173	1.5	214	2.5	296
TRIAD	2	0.5	212	0.75	262	1	291	1.5	377	2.5	545
TRIAD	3	0.5	262	0.75	331	1	379	1.5	497	2.5	736
TRIAD	4	0.5	315	0.75	406	1	473	1.5	625	2.5	927
TRIAD	5	0.5	363	0.75	482	1	561	1.5	756	2.5	1127
TRIAD	6	0.5	418	0.75	558	1	657	1.5	874	2.5	1324
TRIAD	7	0.5	462	0.75	618	1	735	1.5	985	2.5	1507
TRIAD	8	0.5	520	0.75	680	1	823	1.5	1117	2.5	1720
TRIAD	10	0.5	617	0.75	842	1	999	1.5	1375	2.5	2120
TRIAD	12	0.5	702	0.75	969	1	1170	1.5	1606	2.5	2510
TRIAD	14	0.5	798	0.75	1107	1	1339	1.5	1845	2.5	2890
TRIAD	16	0.5	885	0.75	1233	1	1504	1.5	2090	2.5	3277
TRIAD	19	0.5	1022	0.75	1432	1	1751	1.5	2442	2.5	3843
TRIAD	24	0.5	1265	0.75	1792	1	2191	1.5	3075	2.5	4836
QUAD	1	0.5	147	0.75	177	1	206	1.5	256	2.5	365



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELDED - UNARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	66	0.75	80	1	95	1.5	113	2.5	156
PAIR	2	0.5	105	0.75	130	1	156	1.5	220	2.5	299
PAIR	3	0.5	137	0.75	174	1	220	1.5	285	2.5	427
PAIR	4	0.5	156	0.75	220	1	285	1.5	363	2.5	553
PAIR	5	0.5	206	0.75	270	1	397	1.5	441	2.5	682
PAIR	6	0.5	235	0.75	299	1	427	1.5	538	2.5	804
PAIR	7	0.5	254	0.75	345	1	441	1.5	599	2.5	931
PAIR	8	0.5	285	0.75	381	1	521	1.5	682	2.5	1060
PAIR	10	0.5	345	0.75	491	1	631	1.5	854	2.5	1324
PAIR	12	0.5	414	0.75	565	1	744	1.5	1011	2.5	1560
PAIR	14	0.5	457	0.75	650	1	854	1.5	1152	2.5	1797
PAIR	16	0.5	538	0.75	725	1	979	1.5	1324	2.5	2051
PAIR	19	0.5	616	0.75	866	1	1136	1.5	1546	2.5	2412
PAIR	24	0.5	759	0.75	1073	1	1417	1.5	1943	2.5	3059
TRIAD	1	0.5	88	0.75	99	1	126	1.5	154	2.5	226
TRIAD	2	0.5	145	0.75	178	1	221	1.5	286	2.5	424
TRIAD	3	0.5	194	0.75	237	1	301	1.5	397	2.5	600
TRIAD	4	0.5	239	0.75	298	1	386	1.5	508	2.5	784
TRIAD	5	0.5	288	0.75	361	1	472	1.5	625	2.5	973
TRIAD	6	0.5	336	0.75	427	1	555	1.5	744	2.5	1153
TRIAD	7	0.5	381	0.75	482	1	632	1.5	850	2.5	1327
TRIAD	8	0.5	431	0.75	551	1	721	1.5	979	2.5	1513
TRIAD	10	0.5	528	0.75	679	1	902	1.5	1212	2.5	1881
TRIAD	12	0.5	616	0.75	804	1	1061	1.5	1431	2.5	2231
TRIAD	14	0.5	704	0.75	925	1	1222	1.5	1652	2.5	2583
TRIAD	16	0.5	806	0.75	1047	1	1388	1.5	1881	2.5	2951
TRIAD	19	0.5	940	0.75	1224	1	1628	1.5	2208	2.5	3480
TRIAD	24	0.5	1175	0.75	1537	1	2043	1.5	2797	2.5	4383
QUAD	1	0.5	95	0.75	119	1	152	1.5	206	2.5	299

**POLYCAB INDIA LIMITED**

PCC LP No. 03/2021-22 Dtd : 17th August 2021

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	211	0.75	235	1	268	1.5	327	2.5	451
PAIR	3	0.5	271	0.75	302	1	353	1.5	435	2.5	613
PAIR	4	0.5	324	0.75	369	1	431	1.5	545	2.5	758
PAIR	5	0.5	378	0.75	434	1	515	1.5	632	2.5	915
PAIR	6	0.5	418	0.75	505	1	582	1.5	746	2.5	1066
PAIR	7	0.5	476	0.75	558	1	665	1.5	841	2.5	1212
PAIR	8	0.5	542	0.75	616	1	744	1.5	952	2.5	1382
PAIR	10	0.5	640	0.75	753	1	907	1.5	1165	2.5	1696
PAIR	12	0.5	715	0.75	875	1	1038	1.5	1360	2.5	1940
PAIR	14	0.5	828	0.75	985	1	1201	1.5	1552	2.5	2295
PAIR	16	0.5	930	0.75	1109	1	1349	1.5	1750	2.5	2597
PAIR	19	0.5	1063	0.75	1274	1	1558	1.5	2044	2.5	3035
PAIR	24	0.5	1324	0.75	1601	1	1958	1.5	2578	2.5	3818
TRIAD	2	0.5	259	0.75	299	1	338	1.5	421	2.5	581
TRIAD	3	0.5	324	0.75	383	1	442	1.5	560	2.5	794
TRIAD	4	0.5	395	0.75	474	1	549	1.5	688	2.5	1009
TRIAD	5	0.5	463	0.75	561	1	658	1.5	840	2.5	1238
TRIAD	6	0.5	536	0.75	640	1	756	1.5	984	2.5	1453
TRIAD	7	0.5	592	0.75	714	1	848	1.5	1113	2.5	1651
TRIAD	8	0.5	662	0.75	820	1	963	1.5	1271	2.5	1884
TRIAD	10	0.5	796	0.75	991	1	1179	1.5	1559	2.5	2341
TRIAD	12	0.5	921	0.75	1152	1	1378	1.5	1821	2.5	2744
TRIAD	14	0.5	1038	0.75	1309	1	1582	1.5	2102	2.5	3161
TRIAD	16	0.5	1167	0.75	1476	1	1775	1.5	2378	2.5	3587
TRIAD	19	0.5	1352	0.75	1715	1	2082	1.5	2796	2.5	4203
TRIAD	24	0.5	1696	0.75	2158	1	2627	1.5	3493	2.5	5319



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	137	0.75	156	1	192	1.5	235	2.5	332
PAIR	3	0.5	174	0.75	220	1	270	1.5	332	2.5	475
PAIR	4	0.5	220	0.75	270	1	332	1.5	427	2.5	616
PAIR	5	0.5	270	0.75	332	1	414	1.5	521	2.5	759
PAIR	6	0.5	317	0.75	397	1	491	1.5	616	2.5	902
PAIR	7	0.5	363	0.75	441	1	553	1.5	694	2.5	1027
PAIR	8	0.5	414	0.75	505	1	631	1.5	804	2.5	1184
PAIR	10	0.5	505	0.75	631	1	789	1.5	995	2.5	1450
PAIR	12	0.5	587	0.75	744	1	916	1.5	1164	2.5	1735
PAIR	14	0.5	694	0.75	854	1	1073	1.5	1356	2.5	2003
PAIR	16	0.5	775	0.75	964	1	1202	1.5	1546	2.5	2287
PAIR	19	0.5	902	0.75	1136	1	1417	1.5	1814	2.5	2699
PAIR	24	0.5	1136	0.75	1417	1	1783	1.5	2287	2.5	3393
TRIAD	2	0.5	187	0.75	211	1	257	1.5	324	2.5	467
TRIAD	3	0.5	249	0.75	288	1	355	1.5	449	2.5	660
TRIAD	4	0.5	315	0.75	369	1	457	1.5	585	2.5	866
TRIAD	5	0.5	381	0.75	446	1	555	1.5	712	2.5	1065
TRIAD	6	0.5	442	0.75	526	1	658	1.5	856	2.5	1265
TRIAD	7	0.5	502	0.75	599	1	753	1.5	979	2.5	1453
TRIAD	8	0.5	570	0.75	692	1	866	1.5	1116	2.5	1660
TRIAD	10	0.5	712	0.75	852	1	1069	1.5	1382	2.5	2074
TRIAD	12	0.5	836	0.75	1000	1	1260	1.5	1631	2.5	2462
TRIAD	14	0.5	959	0.75	1152	1	1453	1.5	1887	2.5	2850
TRIAD	16	0.5	1080	0.75	1306	1	1650	1.5	2144	2.5	3239
TRIAD	19	0.5	1265	0.75	1530	1	1939	1.5	2538	2.5	3792
TRIAD	24	0.5	1585	0.75	1935	1	2452	1.5	3191	2.5	4803



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						422	613	851	1210
2 Core	107	171	240	362	612	936	1412	1914	2726
3 Core	148	232	337	503	862	1324	1982	2714	3867
4 Core	194	306	441	668	1133	1740	2602	3571	5102
5 Core	235	403							
6 Core	281	441							
7 Core	309	497							
8 Core	357	605							
10 Core	472	747							
12 Core	554	883							
14 Core	643	1020							
16 Core	730	1161							
19 Core	852	1357							
24 Core	1092	1727							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	1700	2230	2829	3519	4288	5666	7096	9317	
3 Core	5449	7145	9056	11271	13736	18070	22663	29651	
4 Core	7143	9362	11945	14867	18131	23846	29876	39208	



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	76	130	231	534	1026	2015

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED,G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	127	197	310	627	1167	2293

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMoured, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMoured CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	2 PAIR	5 PAIR	10 PAIR	20 PAIR		
0.5	100	154	225	300		



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	130
	22 AWG	0.32	143
	20 AWG	0.50	160
	18 AWG	0.80	188
	17 AWG	1.00	203
2 Pair	24 AWG	0.205	188
	22 AWG	0.32	210
	20 AWG	0.50	238
	18 AWG	0.80	293
	17 AWG	1.00	320

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	80
	22 AWG	0.32	90
	20 AWG	0.50	103
	18 AWG	0.80	128
	17 AWG	1.00	140
2 Pair	24 AWG	0.205	120
	22 AWG	0.32	143
	20 AWG	0.50	165
	18 AWG	0.80	213
	17 AWG	1.00	240



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	143
	22 AWG	0.32	157
	20 AWG	0.50	176
	18 AWG	0.80	207
	17 AWG	1.00	223
2 Pair	24 AWG	0.205	207
	22 AWG	0.32	231
	20 AWG	0.50	262
	18 AWG	0.80	322
	17 AWG	1.00	352

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	88
	22 AWG	0.32	99
	20 AWG	0.50	113
	18 AWG	0.80	141
	17 AWG	1.00	154
2 Pair	24 AWG	0.205	132
	22 AWG	0.32	157
	20 AWG	0.50	182
	18 AWG	0.80	234
	17 AWG	1.00	264

**POLYCAB INDIA LIMITED**

PCC LP No. 03/2021-22 Dtd : 17th August 2021

Fire Survival Cables**Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables**

Rate/Mtr.

Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	276	344		419
2.5	344	440		543
4	405	530		663
6	524	701		887
10	740	1013		1295
16	982	1371		1804
25	1400	2017	2429	2651
35	1863	2703	3124	3567
50	2455	3589	4209	4752
70	3413	5014	5866	6640
95	4486	6604	7714	8753
120	5581	8252	9833	10958
150	6834	10120	11692	13428
185	8444	12515	14650	16602
240	10735	15945	18635	21174
300	13299	19757	23057	26261
400	17312	25754	29849	34235

Page 16 of 19

**POLYCAB INDIA LIMITED**

PCC LP No. 03/2021-22 Dtd : 17th August 2021

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	308	378		459
2.5	378	477		583
4	441	568		706
6	561	741		932
10	785	1058		1346
16	1024	1415		1862
25	1453	2075	2493	2717
35	1920	2767	3193	3642
50	2519	3660	4287	4841
70	3491	5105	5965	6746
95	4575	6702	7823	8870
120	5676	8360	9963	11098
150	6948	10252	11840	13593
185	8570	12671	14827	16795
240	10888	16134	18846	21407
300	13479	19977	23304	26542
400	17537	26035	30164	34581

**POLYCAB INDIA LIMITED**

PCC LP No. 03/2021-22 Dtd : 17th August 2021

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	320	396		480
2.5	392	495		608
4	454	586		732
6	576	765		963
10	802	1085		1382
16	1044	1448		1903
25	1486	2125	2553	2784
35	1958	2822	3260	3717
50	2567	3733	4375	4938
70	3554	5199	6078	6873
95	4644	6807	7951	9009
120	5760	8487	10121	11268
150	7055	10416	12035	13813
185	8711	12882	15070	17073
240	11055	16387	19143	21743
300	13677	20274	23656	26938
400	17786	26406	30608	35076



POLYCAB INDIA LIMITED

PCC LP No. 03/2021-22 Dtd : 17th August 2021

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Armoured/FRLS Sheathed FS Aluminium Power Cables

(Rate/Mtr.)

Sq.mm.	3 Core	4 Core
16	490	633
25	660	840
35	799	1031
50	988	1280
70	1350	1757
95	1687	2196
120	2016	2642
150	2399	3143
185	2907	3797
240	3619	4732
300	4355	5716
400	5420	7098